

GREENSGRADER



The GreensGrader is a soil manipulating tool equipped to handle multiple specific operations — scarifying or loosening the soil, leveling and contouring, raking out debris, breaking up clots, and edging along sidewalks, cart paths, etc.

The GreensGrader accomplishes these 5 operations in one piece of equipment, independently or in unison.

The GreensGrader was developed from more than 20 years of thought and on-the-job trial and error. The objective was, and still is, for a machine to perform all of the key operations involved in preparing the soil for seeding and/or sodding.

The GreensGrader, as compared to other equipment on today's market, combines functionality to perform the 5 basic operations to prepare the soil for seeding or sodding in a single unit. The basic requirement for use is a 35-40 HP tractor with category 1 hitch.

SPECIFICATIONS*

Model	790
Main Width	3/8" Steel A-frame
Running Gear	Category 1 three point hitch mount, 40 HP tractor required
Length	43 inches
Width	76.5 inches
Operating Width	72 inches
Height	36 inches
Weight	1,100 lbs.
Grader Blade	Two 72" double beveled cutting edge
Edger Blade	One retractable 1/2" steel angled cutting edge
Scarifying Points	Six 12" spring loaded shanks with 6" chisel point
Spring Tines	22 double torsion, shot peened
Pulverizing Roller	72"x10" diameter hollow core 12 gauge steel w/ expanded metal wrapped exterior
Finish	Powder coat with 6-step pre-wash including de-greaser and anti-rust coating

*All measurements listed within the specifications are from the original design documents. Please confirm the accuracy of such measurements for your own benefit.