

# GREENSWAGON®

Easy transportation for your walk-behind mowers, without the price tag of OEM units. The GreensWagon adapts to the most common mowers from the Big Three and then some.

With an extra wide stance, the GreensWagon provides a stable platform for transport. The heavy gauge steel construction and durable powder-coat finish will deliver many years of reliable service. The perforated deck makes for easy cleanup too. How can you go wrong with this combination?

The GreensWagon comes with an easy slide-out ramp. It takes just seconds to pull the ramp out, load your mower, engage the lock-down mechanism, and slide the ramp back in. You're off to the next green while protecting the drum, height adjustment roller, and bedknives. You'll be assured an accurate cut from the first green to the eighteenth green!

Standard on the GreensWagon are specifically designed "wings". These reinforced wheel housings protect the unit from damaging obstacles. As optional equipment, we produced heavy gauge fenders that further protect the unit and control spray.

Jacobsen 518, 522, 526, TC-22, PGM/Ransom 22


Toro 500, 800, 1000, 1600

Toro Flex 18, 21, 2100

John Deere 180A, 220A

John Deere 180A/B/C, 220A/B/C, 260B/C

Baroness LM 18, 56, 66



## SPECIFICATIONS\*

Model	740
Main Frame	10 gauge steel
Length	70 inches
Width	55 inches
Weight	170 lbs.
Running Gear	2 pneumatic tires (16 x 650-8) Ribbed 2-ply with Roller bearings
Finish	Powder coat with 6-step pre-wash including de-greaser and anti-rust coating
Dimensions	57" W x 16"H x 87" L (with draw-bar)
Shipping Crate	60" x 46" x 21-1/2"
Crated Weight	270 lbs.

\*All measurements listed within the specifications are from the original design documents. Please confirm the accuracy of such measurements for your own benefit.